

### Series 21WN3-4

2-way, internally piloted, normally closed solenoid valve

**3/8"-1/2"**

Pipe Sizes

**8W**

Coil

**2-230 psig**

Operating Pressure



#### Materials of Construction

Body:	<b>Brass</b>
Armature Tube:	<b>Stainless Steel 300</b>
Fixed Core:	<b>Stainless Steel 400</b>
Plunger:	<b>Stainless Steel 400</b>
Spring:	<b>Stainless Steel 300</b>
Shading Ring:	<b>Copper</b>

#### Electrical Connection

Rating:	<b>NEMA 4</b>
Strain Relief Connector:	<b>Model 009</b>
1/2" Conduit Connector:	<b>Model 010</b>
6 ft. Power Cord:	<b>Model GRN100</b>



**Note:** For more detailed specifications, please refer to the datasheet of any individual solenoid valve model within this series.

<b>NBR</b> Sealing Material	<b>14°- 195° F</b> Temperature Range	<b>Air, Inert gas, Water</b> Medium Examples
--------------------------------	---	---

Series 21WN3-4 solenoid valve models, with NBR sealing:

Model #	Pipe Size (Inch)	Orifice Size (Inch)	Flow Factor (CV)	Watt Rating (W)	Min. Pressure (PSI)	Max. Pressure (AC/DC)
21WN3K0B130	3/8"	1/2"	4.10	8	2	230/230
21WN4K0B130	1/2"	1/2"	4.80	8	2	230/230

<b>FKM</b> Sealing Material	<b>14°- 280° F</b> Temperature Range	<b>Air, Inert gas, Water, Synthetic oils</b> Medium Examples
--------------------------------	---	---

Series 21WN3-4 solenoid valve models, with FKM sealing:

Model #	Pipe Size (Inch)	Orifice Size (Inch)	Flow Factor (CV)	Watt Rating (W)	Min. Pressure (PSI)	Max. Pressure (AC/DC)
21WN3K0V130	3/8"	1/2"	4.10	8	2	230/230
21WN4K0V130	1/2"	1/2"	4.80	8	2	230/230