

Series 21WN3-4

2-way, internally piloted, normally closed solenoid valve

3/8"-1/2"

Pipe Sizes

8W

Coil

2-230 psi

Operating Pressure



Materials of Construction

Body:	Brass
Armature Tube:	Stainless Steel 300
Fixed Core:	Stainless Steel 400
Plunger:	Stainless Steel 400
Spring:	Stainless Steel 300
Shading Ring:	Copper

Electrical Connection

Rating:	NEMA 4
Strain Relief Connector:	Model 009
1/2" Conduit Connector:	Model 010
6 ft. Power Cord:	Model GRN100



Note: For more detailed specifications, please refer to the datasheet of any individual solenoid valve model within this series.

NBR Sealing Material	14°- 195° F Temperature Range	Air, Inert gas, Water Medium Examples
--------------------------------	---	---

Series 21WN3-4 solenoid valve models, with NBR sealing:

Model #	Pipe Size (Inch)	Orifice Size (Inch)	Flow Factor (CV)	Watt Rating (W)	Min. Pressure (PSI)	Max. Pressure (AC/DC)
21WN3K0B130	3/8"	1/2"	4.10	8	2	230/230
21WN4K0B130	1/2"	1/2"	4.80	8	2	230/230

FKM Sealing Material	14°- 280° F Temperature Range	Air, Inert gas, Water, Synthetic oils Medium Examples
--------------------------------	---	---

Series 21WN3-4 solenoid valve models, with FKM sealing:

Model #	Pipe Size (Inch)	Orifice Size (Inch)	Flow Factor (CV)	Watt Rating (W)	Min. Pressure (PSI)	Max. Pressure (AC/DC)
21WN3K0V130	3/8"	1/2"	4.10	8	2	230/230
21WN4K0V130	1/2"	1/2"	4.80	8	2	230/230