


Model # 21A2KV45

2-way, direct acting, normally closed solenoid valve



1/4" Pipe Size (Inch)	3/16" Orifice Size (Inch)	0.45 Flow Factor (CV)	12 Watt Rating (W)	0 Min. Pressure (PSI)	170/100 Max. Pressure (AC/DC)
FKM Sealing Material	14° - 280° F Temperature Range	Air, Inert gas, Water, Synthetic oils Medium Examples			

Materials of Construction

Body:	Brass
Armature Tube:	Stainless Steel 300
Fixed Core:	Stainless Steel 400
Plunger:	Stainless Steel 400
Spring:	Stainless Steel 300
Shading Ring:	Copper
Orifice:	Brass

Electrical Connection


Rating:	NEMA 4
Strain Relief Connector:	Model 009
1/2" Conduit Connector:	Model 010
6 ft. Power Cord:	Model GRN100
Inrush VA:	36
Holding VA:	23

Spare Parts

Kit:	KT130KV55
------	------------------

Valve Dimensions

Valve Width(A):	1 3/32"
Valve Length(B):	1 5/8"
Valve Height(C):	3 1/16"
Coil Width(D):	1 7/16"
Coil Length(E):	1 29/32"
Coil Length(F):	2 3/8"



Note: Valve is pictured above with a sample coil, which may or may not reflect the exact specifications of this particular build.