


Model # 21L1K1V25

2-way, direct acting, normally closed solenoid valve



1/8" Pipe Size (Inch)	3/32" Orifice Size (Inch)	0.22 Flow Factor (CV)	14 Watt Rating (W)	0 Min. Pressure (PSI)	435/360 Max. Pressure (AC/DC)
FKM Sealing Material	14° - 280° F Temperature Range	Air, Inert gas, Water, Synthetic oils Medium Examples			

Materials of Construction

Body:	Stainless Steel 316
Armature Tube:	Stainless Steel 300
Fixed Core:	Stainless Steel 400
Plunger:	Stainless Steel 400
Spring:	Stainless Steel 300
Shading Ring:	Gold-plated Copper
Orifice:	Stainless Steel 316

Electrical Connection


Rating:	NEMA 4
Strain Relief Connector:	Model 009
1/2" Conduit Connector:	Model 010
6 ft. Power Cord:	Model GRN100
Inrush VA:	43
Holding VA:	27

Spare Parts

Kit:	KT130KV30-H
------	--------------------

Valve Dimensions

Valve Width(A):	1 3/32"
Valve Length(B):	1 5/8"
Valve Height(C):	3 1/16"
Coil Width(D):	2 1/16"
Coil Length(E):	2 5/32"
Coil Length(F):	2 5/8"



Note: Valve is pictured above with a sample coil, which may or may not reflect the exact specifications of this particular build.